



CCM5G Series Coin Changer

Simple Operation. Maximum Durability.



**Field Tested,
Field Proven.**



Need more change?

Satellite Tube

Ready-to-connect optional Satellite Tube for existing CCM5G 5-tube coin changers. No additional software or hardware required.



Vendnet, Inc.

165 North 10th Street
Waukee, IA 50263
Toll Free: 1.877.4CONLUX or 1.877.426.6589
Email: Conlux@Vendnetusa.com
www.vendnetusa.com

© 2006 MEI. All rights reserved.

Features

Five-Tube Cassette

Greater capacity eliminates change starvation. Sell more product and avoid costly service calls.

Auto Cassette Programming

Cassettes snap into place and coin configurations are automatically recognized by the changer. No programming needed by service technician, no possibility of error. Optimize sales by interchanging cassettes according to vend price.

3-Coin Payout System

Simultaneous payout of three coins speeds transactions and increases throughput in high-volume locations.

Smart Payout

Unit makes multiple attempts to pay out coins if necessary, virtually ensuring transaction; results in fewer service calls.

Anti-Salting Channel

Unique diversion path protects changer and vendor from salt water vandalism and damage.

Memory Back-Up

Non-volatile memory ensures that changer will retain its settings and transaction history in case of a power failure.

No Tools Required

Designed for easy assembly/disassembly and maintenance, even at vend site.

Swing-Open Payout Base

Swing-open cassette base makes for easy collection and change replenishment. No tools required. Expedites cleaning and removal of foreign material.

Last Coin Payout

No dead inventory.

Warranty

Limited 2-year warranty.

Specifications

Interface	Multi-Drop-Bus (M.D.B.)
Operating Voltage	+34VDC
Power Consumption	Standby 0.10A
Operating State	Motor Operation 0.66A Peak Max. 5sec. 0.92A
Operating Temperature Range	5° F (-15° C) to 140° F (+60° C)
Insulation Resistance	20M Ohm or more
Weight	4.2 lb. (1.9 Kg)
Dimensions	HxWxD: 14.83" x 5.43" x 3.23" (376mm x 137mm x 82mm)
Number of Motors	1 Motor – 15VDC
Number of Solenoids	5 for Coin Selection – 15VDC
Coin Acceptance	U.S.: 5¢, 10¢, 25¢, \$1 CAN: 5¢, 10¢, 25¢, \$1, \$2 Switch Selectable for U.S. Only, Canadian Only, or both
Cassette Tube	US-1 Cassette: 1N, 1D, 3Q US-2 Cassette: 2N, 2D, 1Q US-4 Cassette: 1N, 1D, 2Q, 1\$ US-5 Cassette: 2N, 3D