



NBM-3000 Series Bill Validator

Simple Operation. Maximum Durability.



**Field Tested,
Field Proven.**



Features

Vertical Sensing

Magnetic head and optical sensors are positioned away from dirt and protected from salting, resulting in longer life and fewer service calls. Vertical configuration enables easy cleaning, if required.

Anti-Salting System

Built-in protection includes water drain and no electronics in lower chute; saltwater never reaches bill path or electronics.

Pullback, "Yank Cheat", Protection

Motor-driven shutter remains closed when in standby mode, protecting validator from salting, vandalism and cheating.

Unique Bill Stacking Method

Two cam design stacks more bills in less space than conventional validators.

High Acceptance Rate

\$1, \$5 Bills and Coupons.

Optional Security Bezel

Metal bezel protects validator from vandalism. Available factory-installed or as a retrofit kit.

All-Plastic Construction

Lightweight, easy to clean and service.

Swing-Open Stacker

One latch opens bill stacker, making it easy to collect bills.

LED Diagnostics

Indicates status of validator, making field service easier.

Two-Belt Bill Transport

Contributes to longer belt life and easier servicing —system rated at over 200,000 operations.

Warranty

Limited 2-year warranty.

Need more security?

Security Metal Bezel

To protect your NBM-3000 bill validator from vandalism, install the high-security Metal Mask. Available as a service part option or pre-installed on new equipment.



Vendnet, Inc.

165 North 10th Street

Waukee, IA 50263

Toll Free: 1.877.4CONLUX or 1.877.426.6589

Email: Conlux@Vendnetusa.com

www.vendnetusa.com

© 2006 MEI. All rights reserved.

Specifications

Interface	Multi-Drop Bus (M.D.B.)
Operating Voltage	+34VDC
Power Consumption	Standby 0.30A or less
Operating State	Motor Operation 0.60A or less Peak Max. 4 sec. 1.20A or less
Operating Temperature Range	5° F (-15° C) to 140° F (+60° C)
Insulation Resistance	20M Ohm or more
Weight	400 Stacker: 2.24 lb. (1.02 Kg) 700 Stacker: 2.48 lb. (1.12 Kg)
Dimensions	400 Stacker HxWxD: 10.92" x 3.62" x 5.59" (277.3mm x 92.0mm x 141.0mm) 700 Stacker HxWxD: 10.92" x 3.62" x 7.16" (277.3mm x 92.0mm x 181.9mm)
Pullback Prevention	Shutter System
Escrow Function	Available
Front Mask	Bottler Mask and Full-line Mask available
Front Mask Lamp	Available for Bottler Mask and Metal Mask
Bill Acceptance	<ul style="list-style-type: none"> • 2-Way Face-up • \$1, \$5, Coupon • Switch Selectable for \$5 and Coupon